


# SIDECAR M OnOff

"Sidecar is our most compact version of spotlights. It is a traditional side-by-side solution, inspired by the sidecar version of a motorcycle. We created a design that places the point of rotation on the track as central as possible to avoid a big offset from the track, allowing a number of spotlights to visually work well together. Developed and OnOffduced in Sweden".

LED-spotlight with passive cooling system.  
Die cast aluminium body, powder coat painted.  
Integral heatsink. Integral premium driver.  
Low ripple output current <4% to assure camera and scanner friendly performance.  
Rotation 365°. Vertical adjustment +/- 90°.  
Track mounted with 3-circuit adapter.



<b>Class of OnOfffection</b>	IP20, class I
<b>Colours</b>	White, black
<b>Weight total</b>	1020g
<b>Reflector</b>	High efficiency metalized PC
<b>Lifetime</b>	50.000h L80/B10 at Ta 25°C
<b>Mounting</b>	3-circuit universal adaptor
<b>Voltage</b>	220-240V 50/60hz
<b>Qty per MCB</b>	Max 34pcs/MCB 16A type B
<b>Ripple out. current</b>	< 4%. Flicker-free performance
<b>Colour consistency</b>	2 SDCM
<b>Photobiological safety</b>	RG1
<b>Design</b>	Jesper Ståhl
<b>Dimming</b>	Not dimmable



# SIDECAR M OnOff

Description	Reflector	CCT (K)	CRI	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																																																																																																																
LIGHTSOURCE					LUMINAIRE			ART. No.																																																																																																																																																	
WARM WHITE 3000K (930)																																																																																																																																																									
SIDECAR M OnOff 4000lm SP 930 Spot 15°		3000K	92	4670	32W	4290	134	<b>215310</b>	<b>215314</b>																																																																																																																																																
SIDECAR M OnOff 4000lm ME 930 Medium 25°		3000K	92	4670	32W	4290	134	<b>215311</b>	<b>215315</b>																																																																																																																																																
SIDECAR M OnOff 4000lm FL 930 Flood 45°		3000K	92	4670	32W	4290	134	<b>215312</b>	<b>215316</b>																																																																																																																																																
SIDECAR M OnOff 4000lm FL 930 WideFlood 60°		3000K	92	4670	32W	4290	134	<b>215313</b>	<b>215317</b>																																																																																																																																																
SIDECAR M OnOff 5000lm SP 930 Spot 15°		3000K	92	5490	38W	5005	131	<b>215410</b>	<b>215414</b>																																																																																																																																																
SIDECAR M OnOff 5000lm ME 930 Medium 25°		3000K	92	5490	38W	5005	131	<b>215411</b>	<b>215415</b>																																																																																																																																																
SIDECAR M OnOff 5000lm FL 930 Flood 45°		3000K	92	5490	38W	5005	131	<b>215412</b>	<b>215416</b>																																																																																																																																																
SIDECAR M OnOff 5000lm FL 930 WideFlood 60°		3000K	92	5490	38W	5005	131	<b>215413</b>	<b>215417</b>																																																																																																																																																
<table border="1"> <thead> <tr> <th colspan="2">Spot</th> <th colspan="2">4000lm</th> <th colspan="2">5000lm</th> <th colspan="2">Medium</th> <th colspan="2">4000lm</th> <th colspan="2">5000lm</th> <th colspan="2">Flood</th> <th colspan="2">4000lm</th> <th colspan="2">5000lm</th> <th colspan="2">Wideflood</th> <th colspan="2">4000lm</th> <th colspan="2">5000lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>27939</td> <td>32596</td> <td>1</td> <td>0,42</td> <td>13546</td> <td>15804</td> <td>1</td> <td>0,86</td> <td>6129</td> <td>7150</td> <td>1</td> <td>1,19</td> <td>4713</td> <td>5499</td> <td>1</td> <td>1,19</td> <td>4713</td> <td>5499</td> <td>1</td> <td>1,19</td> <td>4713</td> <td>5499</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>6985</td> <td>8149</td> <td>2</td> <td>0,84</td> <td>3387</td> <td>3951</td> <td>2</td> <td>1,72</td> <td>1532</td> <td>1788</td> <td>2</td> <td>2,38</td> <td>1178</td> <td>1375</td> <td>2</td> <td>2,38</td> <td>1178</td> <td>1375</td> <td>2</td> <td>2,38</td> <td>1178</td> <td>1375</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>3104</td> <td>3622</td> <td>3</td> <td>1,25</td> <td>1505</td> <td>1756</td> <td>3</td> <td>2,58</td> <td>681</td> <td>794</td> <td>2,5</td> <td>3,56</td> <td>524</td> <td>611</td> <td>2,5</td> <td>3,56</td> <td>524</td> <td>611</td> <td>2,5</td> <td>3,56</td> <td>524</td> <td>611</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>1746</td> <td>2037</td> <td>4</td> <td>1,70</td> <td>847</td> <td>988</td> <td>4</td> <td>3,44</td> <td>383</td> <td>447</td> <td>3</td> <td>4,76</td> <td>294</td> <td>344</td> <td>3</td> <td>4,76</td> <td>294</td> <td>344</td> <td>3</td> <td>4,76</td> <td>294</td> <td>344</td> </tr> </tbody> </table>										Spot		4000lm		5000lm		Medium		4000lm		5000lm		Flood		4000lm		5000lm		Wideflood		4000lm		5000lm		m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	27939	32596	1	0,42	13546	15804	1	0,86	6129	7150	1	1,19	4713	5499	1	1,19	4713	5499	1	1,19	4713	5499	2	0,56	6985	8149	2	0,84	3387	3951	2	1,72	1532	1788	2	2,38	1178	1375	2	2,38	1178	1375	2	2,38	1178	1375	3	0,84	3104	3622	3	1,25	1505	1756	3	2,58	681	794	2,5	3,56	524	611	2,5	3,56	524	611	2,5	3,56	524	611	4	1,12	1746	2037	4	1,70	847	988	4	3,44	383	447	3	4,76	294	344	3	4,76	294	344	3	4,76	294	344
Spot		4000lm		5000lm		Medium		4000lm		5000lm		Flood		4000lm		5000lm		Wideflood		4000lm		5000lm																																																																																																																																			
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																		
1	0,28	27939	32596	1	0,42	13546	15804	1	0,86	6129	7150	1	1,19	4713	5499	1	1,19	4713	5499	1	1,19	4713	5499																																																																																																																																		
2	0,56	6985	8149	2	0,84	3387	3951	2	1,72	1532	1788	2	2,38	1178	1375	2	2,38	1178	1375	2	2,38	1178	1375																																																																																																																																		
3	0,84	3104	3622	3	1,25	1505	1756	3	2,58	681	794	2,5	3,56	524	611	2,5	3,56	524	611	2,5	3,56	524	611																																																																																																																																		
4	1,12	1746	2037	4	1,70	847	988	4	3,44	383	447	3	4,76	294	344	3	4,76	294	344	3	4,76	294	344																																																																																																																																		
<p>3000K 930 Spectral power distributions</p>																																																																																																																																																									
NEUTRAL WHITE 4000K (940)																																																																																																																																																									
SIDECAR M OnOff 4000lm SP 940 Spot 15°		4000K	92	4770	32W	4360	136	<b>215350</b>	<b>215354</b>																																																																																																																																																
SIDECAR M OnOff 4000lm ME 940 Medium 25°		4000K	92	4770	32W	4360	136	<b>215351</b>	<b>215355</b>																																																																																																																																																
SIDECAR M OnOff 4000lm FL 940 Flood 45°		4000K	92	4770	32W	4360	136	<b>215352</b>	<b>215356</b>																																																																																																																																																
SIDECAR M OnOff 4000lm FL 940 WideFlood 60°		4000K	92	4770	32W	4360	136	<b>215353</b>	<b>215357</b>																																																																																																																																																
SIDECAR M OnOff 5000lm SP 940 Spot 15°		4000K	92	5630	38W	5120	134	<b>215450</b>	<b>215454</b>																																																																																																																																																
SIDECAR M OnOff 5000lm ME 940 Medium 25°		4000K	92	5630	38W	5120	134	<b>215451</b>	<b>215455</b>																																																																																																																																																
SIDECAR M OnOff 5000lm FL 940 Flood 45°		4000K	92	5630	38W	5120	134	<b>215452</b>	<b>215456</b>																																																																																																																																																
SIDECAR M OnOff 5000lm FL 940 WideFlood 60°		4000K	92	5630	38W	5120	134	<b>215453</b>	<b>215457</b>																																																																																																																																																
<table border="1"> <thead> <tr> <th colspan="2">Spot</th> <th colspan="2">4000lm</th> <th colspan="2">5000lm</th> <th colspan="2">Medium</th> <th colspan="2">4000lm</th> <th colspan="2">5000lm</th> <th colspan="2">Flood</th> <th colspan="2">4000lm</th> <th colspan="2">5000lm</th> <th colspan="2">Wideflood</th> <th colspan="2">4000lm</th> <th colspan="2">5000lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>28395</td> <td>33344</td> <td>1</td> <td>0,42</td> <td>13767</td> <td>16167</td> <td>1</td> <td>0,86</td> <td>6229</td> <td>7314</td> <td>1</td> <td>1,19</td> <td>4790</td> <td>5625</td> <td>1</td> <td>1,19</td> <td>4790</td> <td>5625</td> <td>1</td> <td>1,19</td> <td>4790</td> <td>5625</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>7099</td> <td>8336</td> <td>2</td> <td>0,84</td> <td>3442</td> <td>4042</td> <td>2</td> <td>1,72</td> <td>1557</td> <td>1829</td> <td>2</td> <td>2,38</td> <td>1198</td> <td>1406</td> <td>2</td> <td>2,38</td> <td>1198</td> <td>1406</td> <td>2</td> <td>2,38</td> <td>1198</td> <td>1406</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>3155</td> <td>3705</td> <td>3</td> <td>1,25</td> <td>1530</td> <td>1796</td> <td>3</td> <td>2,58</td> <td>692</td> <td>813</td> <td>2,5</td> <td>3,56</td> <td>532</td> <td>625</td> <td>2,5</td> <td>3,56</td> <td>532</td> <td>625</td> <td>2,5</td> <td>3,56</td> <td>532</td> <td>625</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>1775</td> <td>2084</td> <td>4</td> <td>1,70</td> <td>860</td> <td>1010</td> <td>4</td> <td>3,44</td> <td>389</td> <td>457</td> <td>3</td> <td>4,76</td> <td>299</td> <td>352</td> <td>3</td> <td>4,76</td> <td>299</td> <td>352</td> <td>3</td> <td>4,76</td> <td>299</td> <td>352</td> </tr> </tbody> </table>										Spot		4000lm		5000lm		Medium		4000lm		5000lm		Flood		4000lm		5000lm		Wideflood		4000lm		5000lm		m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	28395	33344	1	0,42	13767	16167	1	0,86	6229	7314	1	1,19	4790	5625	1	1,19	4790	5625	1	1,19	4790	5625	2	0,56	7099	8336	2	0,84	3442	4042	2	1,72	1557	1829	2	2,38	1198	1406	2	2,38	1198	1406	2	2,38	1198	1406	3	0,84	3155	3705	3	1,25	1530	1796	3	2,58	692	813	2,5	3,56	532	625	2,5	3,56	532	625	2,5	3,56	532	625	4	1,12	1775	2084	4	1,70	860	1010	4	3,44	389	457	3	4,76	299	352	3	4,76	299	352	3	4,76	299	352
Spot		4000lm		5000lm		Medium		4000lm		5000lm		Flood		4000lm		5000lm		Wideflood		4000lm		5000lm																																																																																																																																			
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																		
1	0,28	28395	33344	1	0,42	13767	16167	1	0,86	6229	7314	1	1,19	4790	5625	1	1,19	4790	5625	1	1,19	4790	5625																																																																																																																																		
2	0,56	7099	8336	2	0,84	3442	4042	2	1,72	1557	1829	2	2,38	1198	1406	2	2,38	1198	1406	2	2,38	1198	1406																																																																																																																																		
3	0,84	3155	3705	3	1,25	1530	1796	3	2,58	692	813	2,5	3,56	532	625	2,5	3,56	532	625	2,5	3,56	532	625																																																																																																																																		
4	1,12	1775	2084	4	1,70	860	1010	4	3,44	389	457	3	4,76	299	352	3	4,76	299	352	3	4,76	299	352																																																																																																																																		
<p>4000K 940 Spectral power distributions</p>																																																																																																																																																									

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.