


SIDECAR M PRO

“Sidecar is our most compact version of spotlights. It is a traditional side-by-side solution, inspired by the sidecar version of a motorcycle. We created a design that places the point of rotation on the track as central as possible to avoid a big offset from the track, allowing a number of spotlights to visually work well together. Developed and produced in Sweden”.

LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral premium driver.
Low ripple output current <4% to assure camera and scanner friendly performance.
Rotation 365°. Vertical adjustment +/- 90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	1020g
Reflector	High efficiency metalized PC
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 34pcs/MCB 16A type B
Ripple out. current	< 4%. Flicker-free performance
Colour consistency	3 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Not dimmable



- White
- Black

SIDECAR M PRO

Description	Reflector	CCT (K)	CRI	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																																								
LIGHTSOURCE					LUMINAIRE			ART. No.																																																																									
WARM WHITE 3000K (930)																																																																																	
SIDECAR M Pro 4000lm SP 930	Spot 15°	3000K	92	4515	35W	4065	115	215310	215314																																																																								
SIDECAR M Pro 4000lm ME 930	Medium 25°	3000K	92	4515	35W	4065	115	215311	215315																																																																								
SIDECAR M Pro 4000lm FL 930	Flood 45°	3000K	92	4515	35W	4065	115	215312	215316																																																																								
SIDECAR M Pro 4000lm FL 930	WideFlood 60°	3000K	92	4515	35W	4065	115	215313	215317																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="3">Spot 15°</th> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 45°</th> <th colspan="3">Wideflood 60°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,26</td> <td>26475</td> <td>1</td> <td>0,43</td> <td>12837</td> <td>1</td> <td>0,86</td> <td>5805</td> <td>1</td> <td>1,19</td> <td>4467</td> </tr> <tr> <td>2</td> <td>0,53</td> <td>6619</td> <td>2</td> <td>0,86</td> <td>3209</td> <td>2</td> <td>1,72</td> <td>1451</td> <td>2</td> <td>2,38</td> <td>1117</td> </tr> <tr> <td>3</td> <td>0,79</td> <td>2942</td> <td>3</td> <td>1,30</td> <td>1426</td> <td>3</td> <td>2,58</td> <td>645</td> <td>3</td> <td>2,97</td> <td>496</td> </tr> <tr> <td>4</td> <td>1,06</td> <td>1655</td> <td>4</td> <td>1,72</td> <td>802</td> <td>4</td> <td>3,44</td> <td>363</td> <td>4</td> <td>4,76</td> <td>279</td> </tr> </tbody> </table>										Spot 15°			Medium 25°			Flood 45°			Wideflood 60°			m	∅	Lux	m	∅	Lux	m	∅	Lux	m	∅	Lux	1	0,26	26475	1	0,43	12837	1	0,86	5805	1	1,19	4467	2	0,53	6619	2	0,86	3209	2	1,72	1451	2	2,38	1117	3	0,79	2942	3	1,30	1426	3	2,58	645	3	2,97	496	4	1,06	1655	4	1,72	802	4	3,44	363	4	4,76	279
Spot 15°			Medium 25°			Flood 45°			Wideflood 60°																																																																								
m	∅	Lux	m	∅	Lux	m	∅	Lux	m	∅	Lux																																																																						
1	0,26	26475	1	0,43	12837	1	0,86	5805	1	1,19	4467																																																																						
2	0,53	6619	2	0,86	3209	2	1,72	1451	2	2,38	1117																																																																						
3	0,79	2942	3	1,30	1426	3	2,58	645	3	2,97	496																																																																						
4	1,06	1655	4	1,72	802	4	3,44	363	4	4,76	279																																																																						
<p>3000K 930 Spectral power distributions</p>																																																																																	
NEUTRAL WHITE 4000K (940)																																																																																	
SIDECAR M Pro 4000lm SP 940	Spot 15°	4000K	92	4490	35W	4045	114	215350	215354																																																																								
SIDECAR M Pro 4000lm ME 940	Medium 25°	4000K	92	4490	35W	4045	114	215351	215355																																																																								
SIDECAR M Pro 4000lm FL 940	Flood 45°	4000K	92	4490	35W	4045	114	215352	215356																																																																								
SIDECAR M Pro 4000lm FL 940	WideFlood 60°	4000K	92	4490	35W	4045	114	215353	215357																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="3">Spot 15°</th> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 45°</th> <th colspan="3">Wideflood 60°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,26</td> <td>26345</td> <td>1</td> <td>0,43</td> <td>12774</td> <td>1</td> <td>0,86</td> <td>5776</td> <td>1</td> <td>1,19</td> <td>4445</td> </tr> <tr> <td>2</td> <td>0,53</td> <td>6586</td> <td>2</td> <td>0,86</td> <td>3194</td> <td>2</td> <td>1,72</td> <td>1444</td> <td>2</td> <td>2,38</td> <td>1111</td> </tr> <tr> <td>3</td> <td>0,79</td> <td>2927</td> <td>3</td> <td>1,30</td> <td>1419</td> <td>3</td> <td>2,58</td> <td>642</td> <td>3</td> <td>2,97</td> <td>494</td> </tr> <tr> <td>4</td> <td>1,06</td> <td>1647</td> <td>4</td> <td>1,72</td> <td>798</td> <td>4</td> <td>3,44</td> <td>361</td> <td>4</td> <td>4,76</td> <td>278</td> </tr> </tbody> </table>										Spot 15°			Medium 25°			Flood 45°			Wideflood 60°			m	∅	Lux	m	∅	Lux	m	∅	Lux	m	∅	Lux	1	0,26	26345	1	0,43	12774	1	0,86	5776	1	1,19	4445	2	0,53	6586	2	0,86	3194	2	1,72	1444	2	2,38	1111	3	0,79	2927	3	1,30	1419	3	2,58	642	3	2,97	494	4	1,06	1647	4	1,72	798	4	3,44	361	4	4,76	278
Spot 15°			Medium 25°			Flood 45°			Wideflood 60°																																																																								
m	∅	Lux	m	∅	Lux	m	∅	Lux	m	∅	Lux																																																																						
1	0,26	26345	1	0,43	12774	1	0,86	5776	1	1,19	4445																																																																						
2	0,53	6586	2	0,86	3194	2	1,72	1444	2	2,38	1111																																																																						
3	0,79	2927	3	1,30	1419	3	2,58	642	3	2,97	494																																																																						
4	1,06	1647	4	1,72	798	4	3,44	361	4	4,76	278																																																																						
<p>4000K 940 Spectral power distributions</p>																																																																																	

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.