


SIDECAR S OnOff

“Sidecar is our most compact version of spotlights. It is a traditional side-by-side solution, inspired by the sidecar version of a motorcycle. We created a design that places the point of rotation on the track as central as possible to avoid a big offset from the track, allowing a number of spotlights to visually work well together. Developed and produced in Sweden”.


LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral premium driver.
Low ripple output current <4% to assure camera and scanner friendly performance.
Rotation 365°. Vertical adjustment +/- 90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	760g
Reflector	High purity aluminium
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 34pcs/MCB 16A type B
Ripple out. current	< 4%. Flicker-free performance
Colour consistency	2 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Not dimmable



- White
- Black



Accessories

Honeycomb louvre Sidecar S **213091**

SIDECAR S OnOff

Description	Reflector	CCT (K)	CRI	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																																																																																																																
				LIGHTSOURCE				ART. No.																																																																																																																																																	
WARM WHITE 3000K (930)																																																																																																																																																									
SIDECAR S OnOff 2000lm SP 930	Spot 15°	3000K	92	2320	16W	2180	136	213110	213114																																																																																																																																																
SIDECAR S OnOff 2000lm ME 930	Medium 25°	3000K	92	2320	16W	2180	136	213111	213115																																																																																																																																																
SIDECAR S OnOff 2000lm FL 930	Flood 40°	3000K	92	2320	16W	2180	136	213112	213116																																																																																																																																																
SIDECAR S OnOff 2000lm WFL 930	Widefl. 60°	3000K	92	2320	16W	2180	136	213113	213117																																																																																																																																																
SIDECAR S OnOff 3000lm SP 930	Spot 15°	3000K	92	3380	25W	3175	126	213210	213214																																																																																																																																																
SIDECAR S OnOff 3000lm ME 930	Medium 25°	3000K	92	3380	25W	3175	126	213211	213215																																																																																																																																																
SIDECAR S OnOff 3000lm FL 930	Flood 40°	3000K	92	3380	25W	3175	126	213212	213216																																																																																																																																																
SIDECAR S OnOff 3000lm WFL 930	Widefl. 60°	3000K	92	3380	25W	3175	126	213213	213217																																																																																																																																																
<table border="1"> <thead> <tr> <th colspan="2">Spot</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Medium</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Flood</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Wideflood</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>14169</td> <td>20548</td> <td>1</td> <td>0,42</td> <td>7887</td> <td>11446</td> <td>1</td> <td>0,74</td> <td>4514</td> <td>6550</td> <td>1</td> <td>1,19</td> <td>2401</td> <td>3488</td> <td>1</td> <td>1,19</td> <td>2401</td> <td>3488</td> <td>1</td> <td>1,19</td> <td>2401</td> <td>3488</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>3542</td> <td>5137</td> <td>2</td> <td>0,84</td> <td>1972</td> <td>2861</td> <td>2</td> <td>1,42</td> <td>1128</td> <td>1637</td> <td>2</td> <td>2,38</td> <td>600</td> <td>872</td> <td>2</td> <td>2,38</td> <td>600</td> <td>872</td> <td>2</td> <td>2,38</td> <td>600</td> <td>872</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>2267</td> <td>2283</td> <td>3</td> <td>1,25</td> <td>876</td> <td>1272</td> <td>3</td> <td>2,18</td> <td>502</td> <td>728</td> <td>3</td> <td>2,97</td> <td>384</td> <td>558</td> <td>3</td> <td>2,97</td> <td>384</td> <td>558</td> <td>3</td> <td>2,97</td> <td>384</td> <td>558</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>885</td> <td>1284</td> <td>4</td> <td>1,70</td> <td>493</td> <td>715</td> <td>4</td> <td>2,91</td> <td>282</td> <td>409</td> <td>4</td> <td>3,56</td> <td>267</td> <td>218</td> <td>4</td> <td>3,56</td> <td>267</td> <td>218</td> <td>4</td> <td>3,56</td> <td>267</td> <td>218</td> </tr> </tbody> </table>										Spot		2000lm		3000lm		Medium		2000lm		3000lm		Flood		2000lm		3000lm		Wideflood		2000lm		3000lm		m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	14169	20548	1	0,42	7887	11446	1	0,74	4514	6550	1	1,19	2401	3488	1	1,19	2401	3488	1	1,19	2401	3488	2	0,56	3542	5137	2	0,84	1972	2861	2	1,42	1128	1637	2	2,38	600	872	2	2,38	600	872	2	2,38	600	872	3	0,84	2267	2283	3	1,25	876	1272	3	2,18	502	728	3	2,97	384	558	3	2,97	384	558	3	2,97	384	558	4	1,12	885	1284	4	1,70	493	715	4	2,91	282	409	4	3,56	267	218	4	3,56	267	218	4	3,56	267	218
Spot		2000lm		3000lm		Medium		2000lm		3000lm		Flood		2000lm		3000lm		Wideflood		2000lm		3000lm																																																																																																																																			
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																		
1	0,28	14169	20548	1	0,42	7887	11446	1	0,74	4514	6550	1	1,19	2401	3488	1	1,19	2401	3488	1	1,19	2401	3488																																																																																																																																		
2	0,56	3542	5137	2	0,84	1972	2861	2	1,42	1128	1637	2	2,38	600	872	2	2,38	600	872	2	2,38	600	872																																																																																																																																		
3	0,84	2267	2283	3	1,25	876	1272	3	2,18	502	728	3	2,97	384	558	3	2,97	384	558	3	2,97	384	558																																																																																																																																		
4	1,12	885	1284	4	1,70	493	715	4	2,91	282	409	4	3,56	267	218	4	3,56	267	218	4	3,56	267	218																																																																																																																																		
<p>3000K 930 Spectral power distributions</p>																																																																																																																																																									
NEUTRAL WHITE 4000K (940)																																																																																																																																																									
SIDECAR S OnOff 2000lm SP 940	Spot 15°	4000K	92	2330	16W	2185	137	213150	213154																																																																																																																																																
SIDECAR S OnOff 2000lm ME 940	Medium 25°	4000K	92	2330	16W	2185	137	213151	213155																																																																																																																																																
SIDECAR S OnOff 2000lm FL 940	Flood 40°	4000K	92	2330	16W	2185	137	213152	213156																																																																																																																																																
SIDECAR S OnOff 2000lm WFL 940	Widefl. 60°	4000K	92	2330	16W	2185	137	213153	213157																																																																																																																																																
SIDECAR S OnOff 3000lm SP 940	Spot 15°	4000K	92	3460	25W	3255	130	213250	213254																																																																																																																																																
SIDECAR S OnOff 3000lm ME 940	Medium 25°	4000K	92	3460	25W	3255	130	213251	213255																																																																																																																																																
SIDECAR S OnOff 3000lm FL 940	Flood 40°	4000K	92	3460	25W	3255	130	213252	213256																																																																																																																																																
SIDECAR S OnOff 3000lm WFL 940	Widefl. 60°	4000K	92	3460	25W	3255	130	213253	213257																																																																																																																																																
<table border="1"> <thead> <tr> <th colspan="2">Spot</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Medium</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Flood</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Wideflood</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>14545</td> <td>21085</td> <td>1</td> <td>0,42</td> <td>8097</td> <td>11738</td> <td>1</td> <td>0,74</td> <td>4631</td> <td>6717</td> <td>1</td> <td>1,19</td> <td>2468</td> <td>3577</td> <td>1</td> <td>1,19</td> <td>2468</td> <td>3577</td> <td>1</td> <td>1,19</td> <td>2468</td> <td>3577</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>3636</td> <td>5271</td> <td>2</td> <td>0,84</td> <td>2024</td> <td>2934</td> <td>2</td> <td>1,42</td> <td>1158</td> <td>1679</td> <td>2</td> <td>2,38</td> <td>617</td> <td>894</td> <td>2</td> <td>2,38</td> <td>617</td> <td>894</td> <td>2</td> <td>2,38</td> <td>617</td> <td>894</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>1616</td> <td>2343</td> <td>3</td> <td>1,25</td> <td>900</td> <td>1304</td> <td>3</td> <td>2,18</td> <td>515</td> <td>746</td> <td>3</td> <td>2,97</td> <td>395</td> <td>572</td> <td>3</td> <td>2,97</td> <td>395</td> <td>572</td> <td>3</td> <td>2,97</td> <td>395</td> <td>572</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>972</td> <td>1318</td> <td>4</td> <td>1,70</td> <td>506</td> <td>734</td> <td>4</td> <td>2,91</td> <td>289</td> <td>420</td> <td>4</td> <td>3,56</td> <td>274</td> <td>397</td> <td>4</td> <td>3,56</td> <td>274</td> <td>397</td> <td>4</td> <td>3,56</td> <td>274</td> <td>397</td> </tr> </tbody> </table>										Spot		2000lm		3000lm		Medium		2000lm		3000lm		Flood		2000lm		3000lm		Wideflood		2000lm		3000lm		m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	14545	21085	1	0,42	8097	11738	1	0,74	4631	6717	1	1,19	2468	3577	1	1,19	2468	3577	1	1,19	2468	3577	2	0,56	3636	5271	2	0,84	2024	2934	2	1,42	1158	1679	2	2,38	617	894	2	2,38	617	894	2	2,38	617	894	3	0,84	1616	2343	3	1,25	900	1304	3	2,18	515	746	3	2,97	395	572	3	2,97	395	572	3	2,97	395	572	4	1,12	972	1318	4	1,70	506	734	4	2,91	289	420	4	3,56	274	397	4	3,56	274	397	4	3,56	274	397
Spot		2000lm		3000lm		Medium		2000lm		3000lm		Flood		2000lm		3000lm		Wideflood		2000lm		3000lm																																																																																																																																			
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																		
1	0,28	14545	21085	1	0,42	8097	11738	1	0,74	4631	6717	1	1,19	2468	3577	1	1,19	2468	3577	1	1,19	2468	3577																																																																																																																																		
2	0,56	3636	5271	2	0,84	2024	2934	2	1,42	1158	1679	2	2,38	617	894	2	2,38	617	894	2	2,38	617	894																																																																																																																																		
3	0,84	1616	2343	3	1,25	900	1304	3	2,18	515	746	3	2,97	395	572	3	2,97	395	572	3	2,97	395	572																																																																																																																																		
4	1,12	972	1318	4	1,70	506	734	4	2,91	289	420	4	3,56	274	397	4	3,56	274	397	4	3,56	274	397																																																																																																																																		
<p>4000K 940 Spectral power distributions</p>																																																																																																																																																									

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.